

Passive HD Transceiver

for AHD / TVI / CVI



Specification

Model	DISS DI-B-01
Properties	
Transmission Signal	1 channel
Transmission Distance	HDCVI 720P: 400m / 1080P: 250m
	HDTVI 720P / 1080P: 250m
	AHD 720P: 350m / 1080P: 200m
Category Type	UTP CAT5 / 5E / 6
Video Transmission Properties and port	
Coaxial Video Connector	BNC-M
Twisted-pair Video Connector	Push-terminal
Compatible Format	AHD / HDTVI / HDCVI
Resolution	720P / 1080P
Anti-interference	>60db
Protection	
ESD	1a contact discharge electricity level 3
	1b air discharge electricity level 3
	Per : IEC61000-4-2
Coaxial Video Connector	2KV(common-code) Per : IEC1000-4-5
UTP Cable Connector	2KV(different-code), 4KV(common-code),Per: IEC1000-4-5
Impedance	
BNC Male	75 ohms
UTP Cable	100 ohms
Physical Properties	
Dimensions (L*W*H)	36.5mm*17.5mm*17.3mm
Shell	ABS
Color	Black
N.W.	22.6G
Stability	
MTBF	>10000H
Environmental	
Operating Temperature	-10°C ~ + 55°C
Storage Temperature	-20°C ~ + 70°C
Humidity	0 – 90% (non-codensing)