



10-port Full Gigabit Managed PoE Switch

VT-G08TP

Overview

The VT-G08TP is a full gigabit L2+ managed PoE fiber switch. It has 8*10/100/1000Base-T RJ45 ports and 2*100/1000Base-X SFP fiber slot ports. Port 1-8 can support IEEE802.3af/at standard PoE power supply. single port PoE power reaches 30W, and the maximum PoE output power is 130W. As a PoE power supply device, it can automatically detect and recognize the power receiving equipment that meets the standard and supply power through the network cable. It can supply power to POE terminal equipment such as wireless AP, webcam, VoIP phone, building visual access control intercom through network cable, to meet the network environment that needs high-density PoE power supply, suitable for hotels, campuses, parks, supermarkets, scenic spots, Factory quarters and SMB small and medium-sized enterprises form a cost-effective network.

The VT-G08TP has L2+ full network management, support IPV4 management, static route full line rate forwarding, security protection mechanism, complete ACL/QoS policy and rich VLAN functions, and is easy to manage and maintain. Supports multiple network redundancy protocols STP/RSTP/MSTP (<50ms) to improve link backup and network reliability. When one-way network fails, communication can be quickly restored to ensure important Uninterrupted communication for applications.

According to the actual application requirements, you can configure multiple application services such as PoE power management, port traffic control, VLAN division, and SNMP through the Web network management mode.

High Performance

- L2+ Managed PoE Switch
- Gigabit access, 1G SFP
- Intelligent PoE power supply
- IEEE802.1Q VLAN
- IGMP Snooping
- VLAN isolation function

Certification

- Lightning protection: 4KV 8/20us
- Protection level: IP30
- CCC ; CE mark
- CE/LVD EN60950
- FCC Part 15 Class B
- RoHS

Easy to use

- Plug and Play design
- No configuration
- Easy to maintain
- LED indicator



10-port Full Gigabit Managed PoE Switch

VT-G08TP

Gigabit access, Gigabit SFP fiber port uplink

- Support “Gigabit Ethernet port and Gigabit SFP port” combination, which enables users to flexibly build networking to meet the needs of various scenarios
- Support non-blocking wire-speed forwarding
- Support full-duplex based on IEEE802.3x and half-duplex based on back pressure

Intelligent PoE power supply

- 8*10/100/1000Base-T RJ45 ports, meeting the needs of security monitoring, teleconferencing system, wireless coverage, and other scenarios
- IEEE802.3af/at PoE standard, without damaging non-PoE devices.
- Priority system for PoE port, it will supply power to the high priority level port first when the power budget is insufficient and avoid overwork of the device
- PoE network management, realize PoE port power allocation, priority setting, port power status viewing, time scheduling, etc

Security

- 802.1X authentication
- Port isolation, Storm control
- IP-MAC-VLAN-Port binding

Strong business processing capability

- IEEE802.1Q VLAN, flexible VLAN division
- QoS, Priority mode based on 802.1P, Port & DSCP, queue scheduling algorithm including Equ, SP, WRR & SP+WRR
- ALC, filter data packet through configuring matching rules, processing operation & time permission, and provide flexible and safe access control
- IGMP V1/V2 and IGMP Snooping
- STP/RSTP/MSTP
- Static and dynamic aggregation

Stable and reliable

- CCC, CE, FCC, RoHS
- Low power consumption, galvanized steel casing, The fan active cooling
- Self-developed power supply, high redundancy design, providing a long term and stable PoE power output
- The user-friendly panel, it can show the device status through the LED indicator of PWR, Link, PoE

Easy operation and maintenance management

- HTTPS, SSLV3, and SSHV1/V2
- RMON, system log, LLDP, and port traffic statistics
- CPU monitoring, memory monitoring, Ping test, and cable diagnose
- Web management, CLI command line (Console, Telnet), SNMP (V1/V2/V3)

Specifications

Model	VT-G08TP
Fixed Port	8*10/100/1000Base-T PoE ports (Data/Power) 2*100/1000Base-X uplink SFP slot ports (Data) 1 * RS232 console port(115200,N,8,1)
Ethernet Port	10/100/1000Base-T(X), auto-sensing, full/half duplex MDI/ MDI-X self-adaption
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP(≤100 meter) 100BASE-TX: Cat5 or later UTP(≤100 meter) 1000BASE-T: Cat5e or later UTP(≤100 meter)
SFP Slot Port	Gigabit SFP optical fiber interface, default matching optical modules (optional order single-mode / multi-mode, single fiber / dual fiber optical module. LC))
Optical Cable/Distance	Multi mode: 850nm /0 ~ 500M, single mode: 1310nm /0 ~ 40KM, 1550nm /0 ~ 120KM.
Chip Parameter	
Network Management Type	L2+
Network Protocol	IEEE802.3 10BASE-T IEEE802.3i 10Base-T IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-T IEEE802.3z 1000Base-X IEEE802.3x
Forwarding Mode	Store and Forward(Full Wire Speed)


Switching Capacity	128Gbps
Forwarding Rate@64byte	14.88Mpps
MAC	8K
Buffer Memory	4.1Mpps
Jumbo Frame	10K
CPU(Hz)	500M
DRAM	1G
Flash	128M
Reset Switch	Yes, One-button factory reset
LED Indicator	Power:PWR (yellow), system :SYS (green), network ;Link (yellow), POE: PoE (green), Fiber port: L/A(green)
Reset Switch	Yes, One-button factory reset
PoE & Power	
PoE Port	Port 1 to 8 IEEE802.3af/at @ POE
PoE Management	Total power limit of PoE power supply PoE output power allocation, off& af &at PoE output priority configuration PoE working status Delay start of power supply Scheduling of PoE operation and time
Power Supply Pin	Default 1/2 (+), 3/6 (-)
Max Power Per Port	30W; IEEE802.3af/at
Total PWR / Input Voltage	130W (AC100-240V)
Power Consumption	Standby:<8W, Full load:<120W
Power Supply	Built-in power supply, AC 100~240V 50-60Hz 2.3A

Physical Parameter	
Operation TEMP / Humidity	-20~+55°C;5%~90% RH Non condensing
Storage TEMP / Humidity	-40~+75°C;5%~95% RH Non condensing
Dimension (L*W*H)	270*181*44.5mm
Net /Gross Weight	<1.7kg
Installation	Desktop, Wall-mounted, 19 inch 1U cabinet
Certification	
Lightning protection / protection level	Lightning protection: 4KV 8/20us; Protection level: IP30
Certification	CCC;CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS;
Network Management Features	
Interface	IEEE802.3X (Full-duplex) Broadcast storm control based on port speed Port real-time traffic management (Flow Interval) The speed limit of the message flow in the access port. The minimum particle size is 1Gbps.
Layer 3 Features	L2+ Network management, IPV4 management Static route, Default route @ 128 pcs, APR @ 1024 pcs
VLAN	VLAN based on the protocol 4K VLAN based on port, IEEE802.1q Port configuration of Access, Trunk, Hybrid

Port Aggregation	LACP, Static aggregation Max 5 aggregation groups and 8 ports per group.
Spanning Tree	STP (IEEE802.1d), RSTP (IEEE802.1w), MSTP (IEEE802.1s)
Multicast	IGMP Snooping v1/v2, Max 1024 multicast groups, Fast log out Multicast VLAN
Port Mirroring	Bidirectional data mirroring based on port
QoS	Flow-based redirection Flow-based rate limiting Flow-based packet filtering 8*Output queues of each port 802.1p/DSCP priority mapping Diff-Serv QoS,Priority Mark/Remark Queue Scheduling Algorithm (SP, WRR, SP+WRR)
ACL	Port-based Issuing ACL ACL based on port and VLAN L2 to L4 packet filtering, matching first 80 bytes message. Provide ACL based on MAC, Destination MAC address, IP Source, Destination IP, IP Protocol Type, TCP/UDP Port, TCP/UDP Port Range, and VLAN, etc.
Security	IP-MAC-VLAN-Port binding ARP inspection,Anti-DoS attack AAA & RADIUS,MAC learning limit Mac black holes,IP source protection Broadcast storm control,Backup for host datum SSH 2.0,SSL,Port isolation,ARP message speed limit User hierarchical management and password protection
DHCP	DHCP Client,DHCP Snooping,DHCP Server


<p>Management</p>	<p>One-key recovery Cable Diagnose,LLDP Web Management (HTTPS) NTP, System work log, Ping Test CPU instant utilization status view Console/AUX Modem/Telnet/SSH2.0 CLI NMS - Smart Network Management System Platform (LLDP+SNMP) Download & Management on FTP, TFTP, Xmodem, SFTP,SNMP V1/V2C/V3</p>
<p>System</p>	<p>Category 5 Ethernet network cable Web browser: Mozilla Firefox 2.5 or higher, Google browser chrome V42 or higher, Microsoft Internet Explorer10 or later; TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, or Mac OS X) installed on each computer in a network</p>

Dimension



- A- Working Indicator
- B- 8*10/100/1000M PoE Ports
- C- Console Port
- D- 2*100/1000M SFP Ports
- E- Power Input Port AC100-240V,50/60Hz

Application



OPTICAL MODULE INFORMATION

1.25G Optical Module	
2630	SFP optical module, 1.25G, multi mode dual fiber 850nm Transmission distance: 550m, LC interface, support DDM function Support hot plug and pull
2632	SFP optical module, 1.25G, single-mode dual fiber 1310nm, transmission distance: 20km, LC interface Support DDM function, support hot plug and pull
2612-T	SFP optical module, 1.25G, single-mode single fiber TX1310nm/RX1550nm, transmission distance: 20km LC interface, support DDM function, support hot plug and pull
2613-R	SFP optical module, 1.25G, single-mode single fiber ,TX1550nm/RX1310nm, transmission distance: 20km LC interface, support DDM function, support hot plug and pull.
2612-T-SC	SFP optical module, 1.25G, single-mode single fiber TX1310nm/RX1550nm, transmission distance: 20km, SC interface, support DDM function, support hot plug and pull.
2613-R-SC	SFP optical module, 1.25G, single-mode single fiber TX1550nm/RX1310nm, transmission distance: 20km, SC interface, support DDM function, support hot plug and pull.
Power Module	
2633	1.25G SFP optical module transfers to 10/100/1000M RJ45 port.