

## VN-LED50A

### 50"(4K) Professional LED Monitor



- HD: 3840\*2160, 4 times higher than normal monitor.
- Turn on the screen to automatically detect the resolution of the input signal in the upper right corner of the screen.
- Clear: delicate and realistic, conveying true colors, showing the true colors.
- Bright: The quality is improved, only for better presentation.
- Adopt industrial screen, high brightness, high contrast.
- High-precision standard regulated power supply, specially designed for industrial equipment, supporting 24 hours × 365 days of uninterrupted work.
- It adopts full metal casing, strong structure, fireproof, moisture proof and shockproof, especially suitable for equipment that is susceptible to electromagnetic interference.
- Adopt 10bit image chip processing technology, high pixel progressive scan, fine texture.
- Support intelligent 3D noise reduction, eliminate afterimage function, dynamic brightness, contrast color optimization technology.
- Apply the world's leading LED driver solution to accurately restore the front-end signal, with a strong sense of reality.
- LED has small volume, low energy consumption, zero radiation, stable image, no impact on the eyes, natural health.
- 6.5 ms extremely fast response, avoiding the tailing phenomenon of images in high speed operation.
- Using nano technology, the picture is more three-dimensional, transparent.
- This machine also comes with a splicing function, no external splicer.

### SPECIFICATIONS

Model	VN-LED50A
Product Type:	Professional Monitor
Screen Size:	50"
Screen Type:	LED
Screen Ratio:	16:9
Brightness	500nit
Contrast Ratio:	5000:1
Response Time:	6.5 ms
Viewing Angle:	≥178 °
Display Color:	1.07B (8-bit + Hi-FRC)
Clearness:	3840*2160
Control Method:	Panel, Infrared
Input Port:	HDMI*2 VGA*1 USB*1 DVI*1 AV*1 232 gorge*1
Output Port:	232 gorge* 2
Audio Output:	2 * Stereo Speakers
Power Supply Mode:	110-220V/
Power frequency:	50-60Hz
Total Power:	130W
Casing:	Professional fireproof iron shell
Installation Method:	Base, Wall Mounting ( Holes:200*200mm)
External Dimensions:	1130mm*660mm*63mm,not including the foot height : 70mm
Product Weight:	10.3kg
Packing Size:	1255mm *790mm *210mm
Gross Weight:	17.3kg
Working Environment Temperature:	Best adapted to 20 °C
Humidity:	10 % ~ 90% RH
Storage Temperature:	-20 °C ~ 60 °C

### DIMENSIONS

