



DI-E200H

2 MP Fixed Turret Camera

- 2 MP turret camera
- EXIR 2.0: advanced infrared technology with 40 m IR distance
- Water and dust resistant (IP67)
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)

▪ Specification

| Camera | |
|--------------------------|--|
| Image Sensor | 2 MP CMOS |
| Max. Resolution | 1920 (H) × 1080 (V) |
| Min. Illumination | 0.01Lux @ (F2.0, AGC ON), 0 Lux with IR |
| Shutter Time | PAL: 1/25 s to 1/50,000 s NTSC: 1/30 s to 1/50,000 s |
| Day & Night | ICR |
| Angle Adjustment | Pan: 0 to 360°, Tilt: 0 to 75°, Rotation: 0 to 360° |
| Signal System | PAL/NTSC |
| Lens | |
| Lens Type | 2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed lens |
| Focal Length & FOV | 2.8 mm, horizontal FOV: 106.4°, vertical FOV: 57.9°, diagonal FOV: 124.6° 3.6 mm, horizontal FOV: 79.6°, vertical FOV: 43.5°, diagonal FOV: 93.7° 6 mm, horizontal FOV: 51.9°, vertical FOV: 30°, diagonal FOV: 58.8° 8 mm, horizontal FOV: 39.9°, vertical FOV: 21.9°, diagonal FOV: 46.5° 12 mm, horizontal FOV: 24.6°, vertical FOV: 13.9°, diagonal FOV: 28.1° |
| Lens Mount | M12 |
| Image | |
| Image Parameters Switch | STD/HIGH-SAT |
| Image Settings | Brightness, Sharpness, Smart IR |
| Frame Rate | TVI: 1080P@30fps, 1080P@25fps CVI: 1080P@30fps, 1080P@25fps AHD: 1080P@30fps, 1080P@25fps CVBS: PAL/NTSC |
| Day/Night Mode | Auto/Color/BW (Black and White) |
| Wide Dynamic Range (WDR) | Digital WDR |
| Image Enhancement | BLC, HLC |
| White Balance | Auto/Manual |
| AGC | Yes |
| Interface | |
| Video Output | Switchable TVI/AHD/CVI/CVBS |
| General | |
| Material | Plastic |
| Dimension | Φ 110 mm × 93.2 mm (Φ 4.33" × 3.67") |
| Weight | Approx. 211 g (0.47 lb.) |
| Operating Condition | -40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation) |
| Communication | Guarding Vision |
| Language | English |
| Power Supply | 12 VDC ± 25% |
| Consumption | Max. 3 W |
| IR Range | Up to 40 m |
| Approval | |
| Protection | IP67 |

▪ **Available Model**







DI-E200H(2.8mm)(C)

DI-E200H(3.6mm)(C)

DI-E200H(6mm)(C)

▪ **Accessory**

▪ **Optional**

| DI-1272ZJ-110-TRS Wall Mount | DI-1275ZJ-SUS Vertical Pole Mount | DI-1276ZJ-SUS Corner Mount | DI-1280ZJ-S Junction Box | DI-1281ZJ-S Inclined Ceiling Mount |
|---|---|---|---|---|
|  |  |  |  |  |
| <p>DI-1280ZJ-TR13</p> | | | | |
|  | | | | |

*All pictures and specifications are for reference only and are subject to change without prior notice.